

LCOM (LUFFT COMMUNICATOR)

The LCOM (Lufft-Communicator) is an industrial PC with the Windows-CE operating system. The following interfaces are available for communication purposes:

- USB
- GPRS modem (RS232)
- Partyline modem (RS232)
- UMB bus (RS485)

Conversion to the following standard protocols can be made in combination with the UMB technology:

- TLS
- NTCIP
- TLS over IP with GPRS (Asfinag)
- DGT (in planning)
- Synop (in planning)

The equipment is configured and measurement data presented on the built-in 7 inch touch screen display. A service PC is therefore no longer required.

Remote access is available for software uploads and data analysis on the LCOM and UMB modules over the GPRS modem.

Technical data	Ref.No.
LCOM Lufft Communicator	8510.EAK
Operating Conditions	
Power supply	20...28VDC
Power consumption	10VA
Ambient temperature	-30°C ... +60°C
Relative humidity	<90% RH
Protection type	IP20
Dimensions	230mm x 130mm x 50mm
USB interface	USB2.0B
GPRS modem interface	RS232 on Wago Cage Clamp
Partyline modem interface	RS232 on Wago Cage Clamp
UMB bus interface	RS485 on Wago Cage Clamp
Display size	7 inch
Display resolution	800 x 480 pixel
Storage conditions	
Ambient temperature	-30°C ...+60°C
Relative humidity	<95% RH
Accessories	
Power supply 230VAC/24VDC (100VA)	8366.USV1
GPRS/GSM modem	8160.GSM

